

## SPOTS

## GRE-261/ GRE-210/ GRE-211/ GRE-212

SPOTS PARA LUMINARIOS, PROYECCIONES DE EXTERIORES, INTERIORES DE MUROS, Y LUCES DE ACENTO



**GRE-261**

DIAMETRO 110mm  
ALTURA 60mm



**GRE-210**

DIAMETRO 70mm  
ALTURA 94mm



**GRE-211**

DIAMETRO 95mm  
ALTURA 100mm



**GRE-212**

DIAMETRO 122mm  
ALTURA 127

### ESPECIFICACIONES

	GRE-261	GRE-210	GRE-211	GRE-212
<b>VOLTAJE</b>	12VDC / 100-240VAC	100-240VAC	100-240VAC	100-240VAC
<b>POTENCIA</b>	12W	6W	7W	12W
<b>(LM/W)</b>	71	70	92	81
<b>LUMENS</b>	860	420	650	980
<b>K</b>	3000-3500 / 5000-5500	3000-3500 / 5000-5500	3000-3500 / 5000-5500	3000-3500 / 5000-5500
<b>ANGULO</b>	60°	60°	60°	60°
<b>VIDA UTIL</b>	50,000 HRS	50,000 HRS	50,000 HRS	50,000 HRS
<b>BASE</b>	AR111	E26	E26	E26
<b>CRI</b>	>70	>70	>70	>70

### COMPONENTES

CUERPO ALUMINIO RECHAZADO

DIFUSOR DE METACRILATO

REFLECTOR DE ALUMINIO FACETADO

DRIVERS DE DISIPACION DE CALOR DE INYECCION DE ALUMINIO